



HI-CAL

LIQUID CALCIUM CHLORIDE

For Calcium Nutrition in Plants and to Amend Soil and Irrigation Water

Information regarding the contents and level of metals in this product is available at the following state web sites:

STATE OF WASHINGTON
<http://www.agr.wa.gov>

STATE OF OREGON
<http://oda.state.or.us/fertilizer>
(Oregon Department of Agriculture web site)

RECOMMENDED APPLICATION RATES

FOR DRIP IRRIGATION:

Apply 10 gallons of Hi-Cal™ liquid calcium chloride per acre inch up to a maximum of 140 gallons of Hi-Cal liquid calcium chloride per acre foot of applied irrigation water per year.

FOR SOIL AMENDMENT:

Apply 25 gallons per acre of Hi-Cal liquid calcium chloride for every ton of gypsum required up to a maximum of 140 gallons of Hi-Cal liquid calcium chloride per acre per year.

FOR WATER RUN:

Apply 40 gallons Hi-Cal liquid calcium chloride for every acre foot of applied water up to a maximum of 140 gallons of Hi-Cal liquid calcium chloride per acre per year.

TO SUPPLEMENT GYPSUM:

Apply 10 to 15 gallons Hi-Cal liquid calcium chloride per acre for every ton of gypsum used up to a maximum of 140 gallons of Hi-Cal liquid calcium chloride per acre per year.

Net Weight: Bulk

Weight Per Gallon = 11.3 lbs

GUARANTEED ANALYSIS

Calcium (Ca).....12%

Derived from Calcium Chloride

CAUTION:

Keep Out of Reach of Children

CONDITIONS OF SALE

- Seller warrants that this product consists of the ingredients specified and is reasonably fit for the purpose stated on this label when used in accordance with direction under normal conditions of use. No one, other than an officer of Seller, is authorized to make any warranty, guarantee, or direction concerning this product.
- Because the time, place, rate of application, and other conditions of use are beyond Seller's control, Seller's liability from handling, storage, and use of this product is limited to replacement of product or refund of purchase price.

**Contact Sales and Technical Support
for specific recommendations.**

**Guaranteed by:
TETRA Technologies, Inc.
25025 Interstate 45 North, Suite 600
The Woodlands, TX 77380
Phone: 281.367.1983**

STORAGE AND USE PRECAUTIONS

GENERAL:

- Avoid mixing with phosphorus or sulfur containing materials, as precipitation may occur.

TANKS:

- Store in polyolefin or polyethylene storage tanks.
- If fiberglass is used, consult manufacturer for compatibility.
- Do not store for extended periods of time in mild steel tanks.
- Although stainless steel tanks are less prone to corrosion than mild steel tanks, they are not recommended for extended storage.

FITTINGS AND VALVES:

- PVC or polypropylene fittings and valves are recommended.
- Do not use nylon fittings and valves.

WARNINGS:

- Harmful if swallowed
- Avoid breathing spray mist
- May cause irritation of nose, throat, and/or skin
- Avoid contact with eyes, skin, and clothing

If swallowed: If victim is conscious, have victim drink water or milk. Never give anything by mouth to an unconscious person. Get medical attention.

If in eyes: Wash eyes with plenty of clear water for at least 15 minutes. Get medical attention.

**DO NOT MIX WITH PHOSPHATE OR
SULFUR CONTAINING SOLUTIONS**